

17. RRFB SHALL INCLUDE ALL EQUIPMENT AND MATERIALS NECESSARY TO PROVIDE A FULLY FUNCTIONAL SYSTEM PER MANUFACTURER'S RECOMMENDATIONS.
18. RRFB FLASH PATTERN SHALL BE COMPLIANT WITH MUTCD, LATEST EDITION, SECTION 4L.03.
19. LOCATION OF PEDESTRIAN PUSH BUTTONS SHALL BE ADA ACCESSIBLE AND MOUNTED NO MORE THAN 10" FROM A FLAT, ACCESSIBLE LANDING SPACE ($\leq 2\%$). SEE MUTCD, LATEST EDITION.
20. AUDIBLE INFORMATION DEVICES (AID) SHALL PROVIDE A LOCATOR TONE, SHALL NOT USE VIBROTACTILE INDICATIONS OR PERUSSIVE INDICATIONS. THE MESSAGE "WARNING LIGHTS ARE FLASHING" SHALL BE SPOKEN TWICE.

	STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION	DRAWING No.
	NOTES - OVERHEAD RECTANGULAR RAPID FLASHING BEACON (RRFB)	R-417I
		APPROVED BY: KK DATE: 2/2026